

TES-1304 Printing Thermometer



FEATURES

- Type K, J, E, T, thermocouple input
- Dual channels with multi-functions (T1, T2 & T1-T2)
- Built-in thermo printer with programmable time

internal setting



SPECIFICATION

Display	4 1/2 digit LCD
Measurement Range	Type K: -200 to 1333 ? (-328 to 2431.4 ?) Type J: -200 to 760 ? (-328 to 1400 ?) Type E: -200 to 705.3 ? (-328 to 1301.5 ?) Type T: -200 to 400 ? (-328 to 752 ?)
Accuracy	Type K: $\pm(0.1\%rdg+0.8 ?)$ (0 to 1333 ? /32 to 2431.4 ?) Type J: $\pm(0.1\%rdg+0.8 ?)$ (0 to 760 ? /32 to 1400 ?) Type E: $\pm(0.1\%rdg+0.8 ?)$ (0 to 705.3 ? /32 to 1301.5 ?) Type T: $\pm(0.1\%rdg+0.8 ?)$ (0 to 400 ? /32 to 752 ?) Type K/J/E/T: $\pm(0.5\%rdg+1 ?)$ (-200 to 0 ? /-328 to 32 ?)
Resolution	0.1 ? / 0.2 ?
Input Protection	60VDC/24Vrms
Sampling Rate	1sec / 1time
Power Supply	6pcs size AAA Alkaline Battery
Battery Life	About 50 hours not including printer
Dimensions	193(L)×74(W)×37(H)mm
Weight	approx. 365g (include batteries)
Accessories	Carrying case, Instruction manual, Batteries, 2 Rolls thermopaper , 9 pin to 25pin Gender charger.



TES Electrical Electronic Corp.