

Tachometer

# MS6208C



- Screen Size: 37\*41mm
- Battery: 1.5V(R03 / LR03) AAA\*3

| Spec                | Range                                         | Accuracy |
|---------------------|-----------------------------------------------|----------|
| Range               | 2.5RPM~99999RPM(rpm / mins)                   |          |
| Resolution          | 2.5RPM~999RPM(0.1RPM), 1000RPM above(1RPM)    |          |
| Display             | 6 digits, max 999999                          |          |
| Accuracy            | ±(0.05%+1)                                    |          |
| Effective Distance  | 50mm~500mm                                    |          |
| Ambient Temp.       | 0~60°C                                        | ±2°C     |
| Sampling Rate       | Approx. 0.8s(over 60 rpm / min)               |          |
| Auto Power Off      | 10 mins(can be canceled)                      |          |
| Working Environment | -10°C~50°C, max 80%RH, indoor altitude <2000m |          |
| Storage Environment | -10°C~50°C, max 70%RH(battery removed)        |          |

| Packaging Information |                                                  |
|-----------------------|--------------------------------------------------|
| Accessories           | Carry bag, Manual, Reflective tape*2, 1.5V AAA*3 |
| Dimension             | 152*55*33mm                                      |
| Weight                | 125g(w/o Battery)                                |
| Quantity              | 40                                               |
| Color Box             | 89*42*210mm                                      |
| Carton Box            | 450*380*230mm                                    |
| SKU No.               | MS6208CCBGLO                                     |
| EAN Code              | 8435394788852                                    |

Laser Distance Meter

# MS6406A



- Single Distance Measurement
- MAX / MIN
- Continuous
- Area / Volume / Pythagorean Measurement
- Addition / Subtract
- Unit Switch
- Measurement Benchmark Switch
- Sound
- Data Clearance
- Error Codes
- Battery Status
- Data Storage 99 Groups
- Battery: 3\*1.5V AAA

| Spec                                   | Range                                              |
|----------------------------------------|----------------------------------------------------|
| Range                                  | 0.05m~60m                                          |
| Accuracy                               | ±2.0mm                                             |
| Measurement Unit                       | m, ft, in                                          |
| Area Unit                              | m <sup>2</sup> , ft <sup>2</sup> , in <sup>2</sup> |
| Laser Type                             | 620~690nm                                          |
| Laser Class                            | Class II, <1mW                                     |
| Single Measurement Time                | 0.25s                                              |
| Working Temperature                    | 0~+40°C                                            |
| Storage Temperature                    | -10~+50°C                                          |
| Battery Type                           | Alkaline AAA, 3*1.5V                               |
| Number of Measurement Per Battery Pack | Approx. 5000                                       |
| Automatic Laser Shut Down              | After 30s                                          |
| Automatic Device Shut Down             | After 180s                                         |

| Packaging Information |                           |
|-----------------------|---------------------------|
| Accessories           | Strip, Manual, 1.5V AAA*3 |
| Dimension             | 120*48*24 mm              |
| Weight                | Approx. 85g               |
| Quantity              | 50                        |
| Color Box             | 75*55*155mm               |
| Carton Box            | 410*325*305mm             |
| SKU No.               | MS6406ACBGLO              |
| EAN Code              | 8435394788982             |

## Laser Distance Meter

# MS6408A



- Single Distance Measurement
- MAX / MIN
- Continuous
- Area / Volume / Pythagorean Measurement
- Addition / Subtract
- Unit Switch
- Measurement Benchmark Switch
- Sound
- Data Clearance
- Error Codes
- Battery Status
- Data Storage 99 Groups
- Battery: 3\*1.5V AAA

| Spec                                   | Range                                              |
|----------------------------------------|----------------------------------------------------|
| Range                                  | 0.05m~80m                                          |
| Accuracy                               | ±2.0mm                                             |
| Measurement Unit                       | m, ft, in                                          |
| Area Unit                              | m <sup>2</sup> , ft <sup>2</sup> , in <sup>2</sup> |
| Laser Type                             | 620~690nm                                          |
| Laser Class                            | Class II, <1mW                                     |
| Single Measurement Time                | 0.25s                                              |
| Working Temperature                    | 0~+40°C                                            |
| Storage Temperature                    | -10~+50°C                                          |
| Battery Type                           | Alkaline AAA, 3*1.5V                               |
| Number of Measurement Per Battery Pack | Approx. 5000                                       |
| Automatic Laser Shut Down              | After 30s                                          |
| Automatic Device Shut Down             | After 180s                                         |

| Packaging Information |                           |
|-----------------------|---------------------------|
| Accessories           | Strip, Manual, 1.5V AAA*3 |
| Dimension             | 120*48*24 mm              |
| Weight                | Approx. 85g               |
| Quantity              | 50                        |
| Color Box             | 75*55*155mm               |
| Carton Box            | 410*325*305mm             |
| SKU No.               | MS6408ACBGLO              |
| EAN Code              | 8435394788999             |

## Laser Distance Meter

# MS6410A



- Single Distance Measurement
- MAX / MIN
- Continuous
- Area / Volume / Pythagorean Measurement
- Addition / Subtract
- Unit Switch
- Measurement Benchmark Switch
- Sound
- Data Clearance
- Error Codes
- Battery Status
- Data Storage 99 Groups
- Battery: 3\*1.5V AAA

| Spec                                   | Range                                              |
|----------------------------------------|----------------------------------------------------|
| Range                                  | 0.05m~100m                                         |
| Accuracy                               | ±2.0mm                                             |
| Measurement Unit                       | m, ft, in                                          |
| Area Unit                              | m <sup>2</sup> , ft <sup>2</sup> , in <sup>2</sup> |
| Laser Type                             | 620~690nm                                          |
| Laser Class                            | Class II, <1mW                                     |
| Single Measurement Time                | 0.25s                                              |
| Working Temperature                    | 0~+40°C                                            |
| Storage Temperature                    | -10~+50°C                                          |
| Battery Type                           | Alkaline AAA, 3*1.5V                               |
| Number of Measurement Per Battery Pack | Approx. 5000                                       |
| Automatic Laser Shut Down              | After 30s                                          |
| Automatic Device Shut Down             | After 180s                                         |

| Packaging Information |                           |
|-----------------------|---------------------------|
| Accessories           | Strip, Manual, 1.5V AAA*3 |
| Dimension             | 120*48*24 mm              |
| Weight                | Approx. 85g               |
| Quantity              | 50                        |
| Color Box             | 75*55*155mm               |
| Carton Box            | 410*325*305mm             |
| SKU No.               | MS6410ACBGLO              |
| EAN Code              | 8435394789002             |

## Laser Distance Meter

# MS6406B



- Single Distance Measurement
- MAX / MIN
- Continuous
- Area / Volume / Pythagorean Measurement
- Addition / Subtract
- Unit Switch
- Measurement Benchmark Switch
- Voice broadcast
- Electronic Level Display
- Data Clearance
- Error Codes
- Battery Status
- Data Storage 99 Groups
- Battery: 3\*1.5V AAA

| Spec                                   | Range                                              |
|----------------------------------------|----------------------------------------------------|
| Range                                  | 0.05m~60m                                          |
| Accuracy                               | ±2.0mm                                             |
| Measurement Unit                       | m, ft, in                                          |
| Area Unit                              | m <sup>2</sup> , ft <sup>2</sup> , in <sup>2</sup> |
| Laser Type                             | 620~690nm                                          |
| Laser Class                            | Class II, <1mW                                     |
| Single Measurement Time                | 0.25s                                              |
| Working Temperature                    | 0~+40°C                                            |
| Storage Temperature                    | -10~+50°C                                          |
| Battery Type                           | 3*1.5V AAA                                         |
| Number of Measurement Per Battery Pack | Approx. 1000                                       |
| Automatic Laser Shut Down              | After 30s                                          |
| Automatic Device Shut Down             | After 180s                                         |

| Packaging Information |                                      |
|-----------------------|--------------------------------------|
| Accessories           | Strip, Manual, USB cable, 1.5V AAA*3 |
| Dimension             | 130*59*28 mm                         |
| Weight                | Approx. 120g                         |
| Quantity              | 50                                   |
| Color Box             | 75*55*155mm                          |
| Carton Box            | 410*325*305mm                        |
| SKU No.               | MS6406BCBGLO                         |
| EAN Code              | 8435394789019                        |

## Laser Distance Meter

# MS6408B



- Single Distance Measurement
- MAX / MIN
- Continuous
- Area / Volume / Pythagorean Measurement
- Addition / Subtract
- Unit Switch
- Measurement Benchmark Switch
- Voice broadcast
- Electronic Level Display
- Data Clearance
- Error Codes
- Battery Status
- Data Storage 99 Groups
- Battery: 3\*1.5V AAA

| Spec                                   | Range                                              |
|----------------------------------------|----------------------------------------------------|
| Range                                  | 0.05m~80m                                          |
| Accuracy                               | ±2.0mm                                             |
| Measurement Unit                       | m, ft, in                                          |
| Area Unit                              | m <sup>2</sup> , ft <sup>2</sup> , in <sup>2</sup> |
| Laser Type                             | 620~690nm                                          |
| Laser Class                            | Class II, <1mW                                     |
| Single Measurement Time                | 0.25s                                              |
| Working Temperature                    | 0~+40°C                                            |
| Storage Temperature                    | -10~+50°C                                          |
| Battery Type                           | 3*1.5V AAA                                         |
| Number of Measurement Per Battery Pack | Approx. 1000                                       |
| Automatic Laser Shut Down              | After 30s                                          |
| Automatic Device Shut Down             | After 180s                                         |

| Packaging Information |                                      |
|-----------------------|--------------------------------------|
| Accessories           | Strip, Manual, USB cable, 1.5V AAA*3 |
| Dimension             | 130*59*28 mm                         |
| Weight                | Approx. 120g                         |
| Quantity              | 50                                   |
| Color Box             | 75*55*155mm                          |
| Carton Box            | 410*325*305mm                        |
| SKU No.               | MS6408BCBGLO                         |
| EAN Code              | 8435394789026                        |

## Laser Distance Meter

# MS6410B



- Single Distance Measurement
- MAX / MIN
- Continuous
- Area / Volume / Pythagorean Measurement
- Addition / Subtract
- Unit Switch
- Measurement Benchmark Switch
- Voice broadcast
- Electronic Level Display
- Data Clearance
- Error Codes
- Battery Status
- Data Storage 99 Groups
- Battery: 3\*1.5V AAA

| Spec                                   | Range                                              |
|----------------------------------------|----------------------------------------------------|
| Range                                  | 0.05m~100m                                         |
| Accuracy                               | ±2.0mm                                             |
| Measurement Unit                       | m, ft, in                                          |
| Area Unit                              | m <sup>2</sup> , ft <sup>2</sup> , in <sup>2</sup> |
| Laser Type                             | 620~690nm                                          |
| Laser Class                            | Class II, <1mW                                     |
| Single Measurement Time                | 0.25s                                              |
| Working Temperature                    | 0~+40°C                                            |
| Storage Temperature                    | -10~+50°C                                          |
| Battery Type                           | 3*1.5V AAA                                         |
| Number of Measurement Per Battery Pack | Approx. 1000                                       |
| Automatic Laser Shut Down              | After 30s                                          |
| Automatic Device Shut Down             | After 180s                                         |

| Packaging Information |                                      |
|-----------------------|--------------------------------------|
| Accessories           | Strip, Manual, USB cable, 1.5V AAA*3 |
| Dimension             | 130*59*28 mm                         |
| Weight                | Approx. 120g                         |
| Quantity              | 50                                   |
| Color Box             | 75*55*155mm                          |
| Carton Box            | 410*325*305mm                        |
| SKU No.               | MS6410BCBGLO                         |
| EAN Code              | 8435394789033                        |